


Stûv 21 - Dimensions 21/85 single face

stûv






Presentation 1 - 2 - 3 - 4 | Accessories | [Dimensions](#) | Achievements | Technical documents



Part-raise
& Low outlet:



Full raise
& High outlet:



Gap for frame and counter-frame fitting.

Optimum range of use: 8 -> 14 KW

Consumption range in wood/hour at 12% humidity (given as a guideline): 2,6 -> 4,6 Kg/h

Weight: 234 kg

Standard smoke exit diameter: 200

Stûv reserve the right to implement product modifications without notice. Measurements are within 3mm tolerance.

WWW.STUV.BE © 4-2008


Stûv 21 - Dimensions 21/85 double face

stûv







Presentation 1 - 2 - 3 - 4 | Accessories | [Dimensions](#) | Achievements | Technical documents



Part-raise
& Low outlet:



Full raise
& High outlet:



Gap for frame and counter-frame fitting.

Optimum range of use: 9 -> 21 KW

Consumption range in wood/hour at 12% humidity (given as a guideline): 2,8 -> 6,6 Kg/h

Weight: 236 kg

Standard smoke exit diameter: 250

Stûv reserve the right to implement product modifications without notice. Measurements are within 3mm tolerance.

WWW.STUV.BE © 4-2008